

UHF Scanner

EYSR160

EYSR160 is a RFID and optical Scanner, supporting both UHF and 2D - codes. Adopting self-developed UHF RFID modules based on the latest Impinj E310 chip and offering excellent single-tag read/write performance, EYSR160 can read RFID tags fast and accurately with a maximum reading range beyond 30cm. The scanner also supports high-performance barcode scanning which can scan barcodes in all conditions, no matter whether they are scratched, dirty, damaged, poorly printed or displayed on the screen.



product SPECIFICATIONS

Physical Characteristics

Dimensions	154.0 x 87.8 x 65.0mm / 6.46 x 3.43 x 2.56in.
Material	Plastic
Keypad	power key / scan key
Button	UHF, 2D, UHF or 2D
LED Indicator	Function: 1 for UHF, 1 for 2D Status: 2 in total, 1 for UHF, 1 for 2D Power: 1 Bluetooth: 1
Buzzer	Voice prompt
Ethernet Interface	RJ45 interface, HID USB

Communication

Bluetooth	Bluetooth 5.0 (Optional)
-----------	--------------------------

User Environment

Dropping	1.5m
----------	------



Data Collection

Barcode Scanning

Scan Engine	2D Scanner
Min.Resolution	Code 39 - 4mil, UPC - 7.8mil (60%), PDF417 - 5mil, Datamatrix - 5mil

UHF

Engine	CM-3N module based on Impinj E310
Protocol	EPCglobal C1G2 (ISO18000-6C)
Frequency	920-925MHz / 902-928MHz / 865-868MHz
Output Power	1-25dBm
Output Power Precision	±1dBm
Output Power Flatness	±1dBm
Antenna	Circular Polarized Antenna
R/W range	>30cm (Tag: Alien H3)

Accessories (Optional)

USB Cable	TYPE-A, RJ45
Power Supply	5V 2A

Headquarter

Address: Via Galliera, 219 - 40050 Funo di Argelato (BO) - Italy
Phone: + 39 051 862369
Email: info@easyrfid.it

R&D / Product Plant

Address: Via Resistenza, 7/4 - 41011 Campogalliano (MO) - Italy
Phone: + 39 059 851001