

## Fixed UHF Reader

# EYUR4



EYUR4 is a high-performance four-channel fixed UHF reader. With Impinj E710 / R2000 chip in its core module, EYUR4 guarantees high stability, excellent anti-electromagnetic interference capability, and great heat dissipation performance. This device meets every requirement for the integration in both indoor and outdoor environments, in situations with strict RFID application standards such as warehouse management, retail, automotive.

# product SPECIFICATIONS

### Physical Characteristics

**Dimensions** 102.8 mm(L) x 102.8 mm(W) x 28 mm(H)

Weight 329 g / 11.6 oz. (without antenna)

Material Aluminium alloy
Input Voltage DC 9V - 12V

Standby Current < 30mA

Work Current 800mA +/-5% @ DC 12V Input

Comm Interface RS-232 / RJ45

**GPIO** 2 channel input optical coupling, 1 channel

output electric relay, 1 channel output optical

coupling (in reserve)

Baud Rate 115200 bps
Cooling Mode Air cooling

Ethernet interface 10/100 Base-T Ethernet (RJ45)

#### User Environment

Operating Temp.  $-13^{\circ}$ F to  $149^{\circ}$ F /  $-25^{\circ}$ C to  $65^{\circ}$ C Storage Temp.  $-40^{\circ}$ F to  $185^{\circ}$ F /  $-40^{\circ}$ C to  $85^{\circ}$ C

**Humidity** 10%- 95%

#### **Developing Environment**

SDK Windows, Linux, Android

#### **UHF**

Engine CM710-4 module based on Impinj E710

CM2000-4 module based on Impinj Indy R2000

**Protocol** EPC global UHF Class 1 Gen 2 / ISO 18000-6C

**Frequency** 865-868 MHz / 920-925 MHz / 902-928 MHz

**Output Power** 1W (30dBm, support +5~+30dBm adjustable)

2W Optional (33dBm, support +10~+33dBm adjustable, for Latin America, etc.)

Output Power Precision +/- 1dB

Output Power Flatness +/- 0.2dB

Receive Sensitivity < -84dBm

**Fastest Read Rat** 900+ tags/sec

RSSI Supported

Ambient Temp Monitor Supported

Antenna Detector Supported

**Antenna** Supporting a variety of antennas, such as 6dBic,

9dBic

Antenna Port 4 channel 50Ω SMA port





Phone: + 39 051 862369 Email: info@easyrfid.it